



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name Zinc Sterate Mold Release

Product Code A-501

Intended Use(s) : For professional use only

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated
5642 White Mountain Ave
PO Box 1339
Lakeside AZ 85929
928-537-8387
www.factor2.com
sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

928- 368-7502

SECTION 2: HAZARD IDENTIFICATION

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Aerosols	Category 2
Gases under pressure	Liquefied gas
Skin Irritation	Category 2
Skin sensitization	Category 1
Eye Irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity single exposure	Category 3 (Central nervous system)
Specific target organ Toxicity repeated exposure	Category 2
Aspiration hazard	Category 1

Label Elements - Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & supplemental Information





Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

Signal word

Danger

Hazard statements


- H223 Flammable aerosol
- H280 Contains gas under pressure; may explode if heated
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H361 Suspected of damaging fertility or the unborn child
- H336 May cause drowsiness or dizziness
- H304 May be fatal if swallowed and enters airways
- H373 May cause damage to organs through prolonged or repeated exposure

Precautionary statements

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P281 Use personal protective equipment as required.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well ventilated area
- P264 Wash thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response: Response

- P308+P313+P314 If exposed, concerned, or feel unwell: Get medical advice/attention
- P301+P310 If Swallowed: Immediately call a poison center or doctor
- P331 Do not induce vomiting
- P302 + P352 If on skin: Wash with plenty of soap and water..
- P332+P313 If skin irritation occurs: Get medical advice / attention.
- P362 Take off contaminated clothing and wash before reuse.
- P304+P340 If Inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a poison center/doctor if you feel unwell
- P305+P351+P338 If in eyes Rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P333+P313 If skin irritation or rash occurs: Get medical advice/ attention
- P403+P405 Store in well ventilated place.. Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
- P501 Dispose of contents/container in accordance with local/regional regulations.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Name	Product Identifier CAS No	%
1,1,-Difluoroethane (HFC-152a)	75-37-6	35-45 %
Dimethyl Ether	115-10-6	35-45 %
Isohexane	92112-69-1	20-30 %
Cyclopentane	287-92-3	0-3 %
N_Hexane	110-54-3	0-2 %
Zinc Stearate	557-05-1	2-5 %

SECTION 4: FIRST AID MEASURES

Eye Contact	Flush with warm water for 15 minutes. Seek medical attention.
Skin Contact	Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.
Inhalation	Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.
Ingestion	Do not induce vomiting. Get medical attention immediately. DO NOT GIVE AN UNCONCIOUS OR CONVULSING PERSON ANYTHING BY MOUTH!

SECTION 5: FIRE FIGHTING MEASURES

Flash Point Flash point of propellant <0 degrees F.

Flammable limits in air, % by volume:

Upper 18 % (VOL.) Gas in air (propellant portion)
Lower 3.4 % (VOL.) Gas in air (propellant portion)

Extinguishing Media

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Unusual Fire & Explosion Hazards

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

Special Fire Fighting Procedures

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed

SECTION 7: HANDLING AND STORAGE

Handling

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage

Store in a cool, dry area, away from heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Protective Equipment

Use synthetic gloves if necessary, to prevent excessive skin contact. Do not wear



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

contacts and always use ANSI approved safety glasses or splash shield.

Engineering Controls

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Respiratory Protection

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above 1000 ppm, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised

We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Exposure guidelines:

Ingredients	CAS #	Percent	Exposure Limits
1,1,-Difluoroethane (HFC-152a)	75-37-6	35-45 %	1000 ppm 8 hour TWA (1)
Dimethyl Ether	115-10-6	35-45 %	1000 ppm 8 hour TWA (1)
Iso haexane	92112-69-1	20-30 %	OSHA (TWA) 500 ppm ACGIH (TWA) 500 ppm
Cyclopentane	287-92-3	0-3 %	OSHA (TWA) 500 ppm ACGIH (TWA) 600 ppm
N-Hexane	110-54-3	.0-4 %	OSHA (TWA) 500 ppm ACGIH (TWA) 50 ppm
Zinc Stearate	557-05-1	2-5 %	OSHA (PEL) 10 mg/m ACGIH (TLV) 10 mg/m

(1) Supplier Acceptable Exposure Limit

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (Based on typical material)

Appearance	Whiter mist as dispensed from aerosol can.
Odor	Negligible
Evaporation Rate	Ether = 1 Slower
PH	NA
Melting/Freezing point	NE
Initial Boiling point and boiling range	NE
Flash Point	Flash point of propellant < 0°F
Flammability	Flammable



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

Vapor pressure	>30 psi
Vapor density	>1 (Air=1)
Relative density	NE
Solubility	negligible
Partition coefficient	NE
Auto-ignition temperature	NE
Decomposition temperature	NE
Viscosity	NA
Flammable limits in air, % by volume	
Upper	18 % (VOL.) Gas in air (propellant portion)
Lower	3.4 % (VOL.) Gas in air (propellant portion)

SECTION 10: STABILITY AND REACTIVITY DATA

Stability	Stable
Conditions to Avoid	Heat, spark, and open flame
Incompatibility	Strong-Oxidizing Agents
Hazardous Decomposition	Combustion will produce Carbon Monoxide, Carbon Dioxide and nitrogen-oxygen compounds.
Hazardous Polymerization	Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Component Toxicological Information:

Zinc Stearate 557-05-01	Oral LD50 Rat >10,000 mg/kg
N-Hexane 110-54-3	Oral LD 50 Rat: 25 g/kg
Inhalation	LC 50 Rat: 48000 ppm, 4 h
Dermal	LD 50 Rabbit: > 1.3 g/kg
Dimethyl Ether 115-10-6	
Inhalation	LC50: 164,000 ppm in rats 4 h
HFC-152a 75-37-6	
Oral	ALD >1500 mg/kg in rats
Inhalation	ALC 4 hour 383,000 ppm in rats

Reproductive toxicity assessment n-hexane

Some evidence of adverse effects on sexual function and fertility, and/or development, based on animal experiments



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

Additional Information

Prolonged or repeated contact with skin may cause: defatting, dermatitis. Contact with eyes can cause; Redness, blurred vision, provokes tears. Effects due to ingestion may include: gastrointestinal discomfort, central nervous system depression, lung irritation, chest pain, pulmonary edema, giddiness, slowed reaction time, slurred speech, headache, dizziness, drowsiness unconsciousness.

SECTION 12: ECOLOGICAL INFORMATION

110-54-3

Toxicity to fish LL50 Pimephales promelas (fathead minnow) – 2.5 mg/l – 96 h

Toxicity to daphnia and other aquatic Invertebrates

EL50(Daphnia magna (Water flea): 3,878 mg/l 48 h

Toxicity to algae EL50 Chlorella vulgaris (Fresh water algae) – 12840 mg/l 3h
EC50 –Skeletoma – 0.30 mg/l – 8h

75-37-6

Toxicity to fish LC50 / 96 h / Fish (unspecified species): 295,783 mg/l

Toxicity to aquatic invertebrates EC50 / 48 h / Daphnia: 146,695 mg/l

115-10-6

Toxicity to fish LC50/96 h/Poecilia reticulata (guppy): >4000 mg/l

Toxicity to aquatic invertebrates EC50/48 h/Daphnia: >4000 mg/l
LC50/48 h/Daphnia: 755,549 mg/l

Chronic toxicity to fish Due to its physical properties, there is no potential for adverse effects.

Ecotoxicity Assessment

Product Name IMS Zinc Stearate

Product Code 131398

SECTION 13: DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and reinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

SECTION 14: TRANSPORT INFORMATION

Aerosols (limited quantity),

Class 2.1,

ERG 126

AIR (IATA)

Aerosols (limited quantity),

Class 2.1,

ERG 126,

UN No. 1950

Vessel

Aerosol (Limited Quantity),

Class 2.1,

UN No 1950

SECTION 15: REGULATORY INVORMATION

Environmental Regulations

SARA 302/304

None

SARA 311/312:

Immediate (x) Delayed (x) Fire (x) Reactive () Sudden Release of Pressure (x)

Section 313

n-hexane 110-54-3 1-1.5%

California Prop. 65

All the chemicals used in this product are TSCA listed.

Check with your local regulators to be sure all local regulations are met.

SECTION 16: OTHER INFORAMTION

Hazard ratings

This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

NFPA **Level 2 Aerosol**

HMIS **Health: 2**
Flammability: 4
Reactivity: 0



Factor II, Incorporated

The Art, Science and Technology of
Silicones and Prosthetics...

Safety Data Sheet

Product Code: A-501

Revision Date: 2/12/2018

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

DISCLAIMER / STATEMENT OF LIABILITY:

This is a computer-generated document that is valid without a signature.

The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document.