



Factor II Inc. encourages the end user to read this document entirely and understand all sections of this SDS sheet prior to use. There is important information regarding this product. The end user is expected to follow all precautions outlined in this SDS.

## **SECTION 1: IDENTIFICATION**

### **PRODUCT IDENTIFIER**

**Product Name :** Silicone Fluid

**Product Code :** A-315

**Intended Use(s) :** Light Silicone solvent/Low Viscosity Silicone Fluid

### **CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET**

Factor II, Incorporated  
5642 White Mountain Ave  
PO Box 1339  
Lakeside AZ 85929  
928-537-8387  
[www.factor2.com](http://www.factor2.com)  
[sales@factor2.com](mailto:sales@factor2.com)

### **EMERGENCY TELEPHONE NUMBERS**

928- 368-7502

## **SECTION 2: HAZARD(S) IDENTIFICATION**

### **GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 2), H225

Acute aquatic toxicity (Category 1), H400

Aquatic Chronic (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **Hazard Symbol**



### **Signal word**

Danger



- Hazard statement(s)** H225 Highly flammable liquid and vapour.  
H400 – Very toxic to aquatic life  
H411 – Toxic to aquatic life with long lasting effects.
- Precautionary statement** P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
P391 Collect spillage.  
P403+P233+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/ container to an approved waste disposal plant.

**2.3 Other Hazards**

Other hazards not contributing      Exposure may aggravate pre-existing eye, skin, or  
To the classification      respiratory conditions.

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS****3.1 Substances**

Name      A-315  
CAS-No.      107-46-0

Name	Product Identifier	%	GHS-US Classification
Hexamethyldisiloxane	(CAS-No.) 107-46-0	100	Flamm. Liq. 2, H225 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

For the full text of the H-Statements mentioned in this section, see Section 16.

**3.2 Mixtures**

Not Applicable

**SECTION 4: FIRST-AID MEASURES****4.1 Description of first aid measures**

First aid measures general      Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. (Show the label when possible).



First-aid measures after inhalation	When symptoms occur; go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.
First-aid measures skin contact	Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.
First-aid measures after eye contact	Rinse cautiously for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

#### **4.2 Most important symptoms and effects, both acute and delayed**

Systems/effects	Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	Prolonged exposure may cause irritation.
Symptoms/effects after skin contact	Prolonged exposure may cause skin irritation.
Symptoms/effects after eye contact	May cause slight irritation to eyes.
Symptoms/effects after ingestion	Ingestion may cause adverse effects.
Chronic symptoms	None expected under normal conditions of use.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

If exposed or concerned get medical advice or attention. If medical advice is needed, have product container or label at hand.

### **SECTION 5: FIRE-FIGHTING MEASURES**

#### **5.1 Extinguishing media**

Suitable extinguishing media	Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ). Water may be ineffective, but water should be used to keep fire-exposed container cool.
Unsuitable extinguishing media	Do not use heavy water stream. A heavy water stream may spread burning liquid.

#### **5.2 Special hazards arising from the substance or mixture**

Fire Hazard	Highly flammable liquid vapor.
Explosion Hazard	May form flammable or explosive vapor-air mixture.
Reactivity	Reacts violently with strong oxidizers. Increased risk of fire or explosion.

#### **5.3 Advice for Fire Fighters**

Precautionary measures fire:	Exercise caution when fighting any chemical fire.
Firefighting instructions:	Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting:	Do not enter fire area without proper protective equipment, including respiratory protection.
Other information:	Do not allow the product to be released into the environment.



## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1 Personal precautions, protective equipment, and emergency procedures**

#### General measures

Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breath vapor, mist or spray.

#### **6.1.1 For non-emergency personnel**

##### Protective equipment

Use appropriate personal protective equipment (PPE)

##### Emergency procedures

Evacuate unnecessary personnel. Stop leak if safe to do so.

#### **6.1.2 For emergency responders**

##### Protective equipment

##### Emergency procedures

Equip cleanup crew with proper protection. Ventilate area. Eliminate ignition sources. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

### **6.2 Environmental precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

### **6.3 Methods and material for containment and clean up**

#### For containment

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill, or leak area in all directions.

#### Methods for clean up

Absorb and/or contain spill with inert material. Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Contact competent authorities after spill.

### **6.4 Reference to other sections**

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## **SECTION 7: HANDLING AND STORAGE**



### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray. Take precautionary measures against static discharge. Use only non-sparking tools.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.
- Storage conditions : Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.
- Incompatible products : Strong acids, strong bases, strong oxidizers.

### 7.3. Specific end use(s)

Ideal for providing lubricious and/or hydrophobic coating. For professional use only.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1. Control parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

### 8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.
- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.





Materials for protective clothing	: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical safety goggles.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Other information	: When using, do not eat, drink or smoke.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Colorless
Color	: No data available
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 100 °C (212 °F)
Flash point	: -1.11 °C (30 °F)
Auto-ignition Temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Specific Gravity	: < 1 (water=1)
Solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity	: No data available

**9.2. Other information**

VOC content : &lt; 1 %

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

**10.2. Chemical stability**

Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizers.

**10.6. Hazardous decomposition products**Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Acute toxicity : Not classified

<b>Hexamethyldisiloxane (107-46-0)</b>	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (ppm)	15956 ppm/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Prolonged exposure may cause irritation.

Symptoms/effects after skin contact : Prolonged exposure may cause skin irritation.

Symptoms/effects after eye contact : May cause slight irritation to eyes.

Symptoms/effects after ingestion : Ingestion may cause adverse effects.

Chronic symptoms : None expected under normal conditions of use.

**SECTION 12: ECOLOGICAL INFORMATION****12.1. Toxicity**

Ecology - general : Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.





<b>Hexamethyldisiloxane (107-46-0)</b>	
LC50 fish 1	3.02 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
<b>12.2. Persistence and degradability</b>	
A-315	
Persistence and degradability	May cause long-term adverse effects in the environment.
<b>12.3. Bioaccumulative potential</b>	
A-315	
Bioaccumulative potential	Not established.
<b>Hexamethyldisiloxane (107-46-0)</b>	
BCF fish 1	1300
Log Pow	4.2

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Product/Packaging disposal : Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

### SECTION 14: TRANSPORT INFORMATION

In accordance with DOT / IMDG / IATA

#### 14.1. UN number

UN-No.(DOT) : 1993  
DOT NA no. UN1993

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s. (Hexamethyldisiloxane)  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid







DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: II - Medium Danger
DOT Special Provisions (49 CFR 172.102)	: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F). TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
Marine pollutant	: Marine pollutant



#### 14.3. Additional information

Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

#### Transport by sea

DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
-----------------------------	---

MFAG-No	: 127;128
---------	-----------

**Air transport**

DOT Quantity Limitations : 5 L

Passenger aircraft/rail (49 CFR  
173.27)

DOT Quantity Limitations : 60 L

Cargo aircraft only (49 CFR  
175.75)**SECTION 15: REGULATORY INFORMATION****15.1. US Federal regulations**

All components of this product are listed or exempted from being listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

<b>A-315 (107-46-0)</b>	
SARA Section 311/312 Hazard Classes	Fire hazard

**15.2. US State regulations**

<b>Hexamethyldisiloxane (107-46-0)</b>
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

**California Prop. 65 Components**


This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**SECTION 16: OTHER INFORMATION**

Full text of H-phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Flam. Liq. 2	Flammable liquids Category 2
H225	Highly flammable liquid and vapor
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

1 - Materials that, under emergency conditions, can cause significant irritation.



NFPA health hazard

NFPA fire hazard

NFPA reactivity

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

0 - Material that in themselves are normally stable, even under fire conditions.

Hazard Rating

Health

Flammability

Physical

: 1 Slight Hazard - Irritation or minor reversible injury possible

: 3 Serious Hazard

: 0 Minimal Hazard

**Factor II, Inc. Disclaimer & Statement of Liability**

*This is to certify that the above designated material has been tested and did comply with the listed specifications (with listed exceptions) when supplied in original container. The material is subject to the conditions listed on the invoice. The above is a copy of information on file. The lot acceptance data are available for examination. This is a computer-generated document that is valid without a signature. The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document.*

*Factor II, Inc. urges each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or*



## Factor II, Incorporated

The Art, Science and Technology of  
Silicones and Prosthetics...

## Safety Data Sheet

A-315

Date of Issue: 08-01-2014  
Revision Date: 06-28-2021

*individuals who are experts in ventilation, toxicology and/or fire prevention as necessary or appropriate to the use and understanding of the data contained in this SDS. To promote safe handling each customer or recipient should 1) notify and furnish its employees, agents, contractors, customers and/or others whom it knows or believes will use this material of the information regarding hazards or safety, and 2) request its customers to notify their employees, customers, and other users of the product of this information.*