

The Art, Science and Technology of Silicones and Prosthetics...

Product Code: B-206 Revision Date: 7/01/2020

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name Adhesive Remover

Product Code B-206

Intended Use(s) : For professional use only

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated 5642 White Mountain Ave PO Box 1339 Lakeside AZ 85929 928-537-8387 www.factor2.com sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

928-368-7502

SECTION 2: HAZARD IDENTIFICATION

Hazard Classification

Flammable Liquid	Category 4
Signal Word	Warning

Hazard Statement(s) H227 Combustible liquid

Precautionary Statement(s)

P210 Keep away from flames and hot surfaces. –No Smoking.
P280 Wear protective gloves/eye protection/face protection
P370+P378 In case of fire: Use dry chemical, carbon dioxide (CO2), water spray for extinction.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with all applicable local, state and federal regulations.

Potential Health Effects

Inhalation

High vapor concentrations may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects.



Safety Data Sheet

The Art, Science and Technology of Silicones and Prosthetics...

Factor II, Incorporated

Product Code: B-206 Revision Date: 7/01/2020

Eye Contact	May cause irritation.
Skin Contact	Repeated or prolonged contact may cause skin dryness or cracking.
Ingestion	May be aspirated and cause lung damage.

National Fire Protection Association (NFPA) (estimated)

Health-1

Reactivity-0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Flammability-2

Chemical Name	CAS Number	Percent (by weight)	Exposure Limit in Air (TWA - 8 hours a day/ 5-day work week)
Odorless Mineral Spirits Naphtha (petroleum), hydrotreated heavy	64742-48-9	<100%	1200 mg/m3 / 175 ppm (Exxon)

Listed Carcinogens: The following components, present at concentrations of $\ge 0.1\%$ are listed as carcinogens or potential carcinogens by either the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), OSHA or ACGIH: None.

SECTION 4: FIRST AID MEASURES

Inhalation	Remove from further exposure. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a medical device or use mouth-to-mouth resuscitation.
Eyes	Immediately flush eyes with plenty of water. If irritation occurs, get medical attention.
Skin	Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.
Ingestion	Seek immediate medical attention. Do not induce vomiting.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing Media

Water fog, CO2, foam or dry chemical

Special Fire Fighting Procedures

Hazardous material. Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. Vapors are flammable and heavier than air,



Safety Data Sheet Product Code: B-206 Revision Date: 7/01/2020

The Art, Science and Technology of Silicones and Prosthetics...

may travel across the ground and reach remote ignition sources causing a flashback fire danger.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Protection

Avoid contact with spilled material. See Section 4 for First Aid advice. Use personal protection recommended in Section 8 of the SDS.

Notification Procedure

U.S. regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity which could reach any waterway. The National Resource Center can be reached at (800) 424-8802.

Spill Cleanup Methods

Prevent entry into sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

SECTION 7: HANDLING AND STORAGE

Handling Store at controlled room temperature between 59-86oF (15-30oC)

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls Adequate ventilation so that exposure limits are not exceeded.

Respiratory Protection

Not applicable; aerosol formation is extremely unlikely for normal use. When handling large quantities an approved respirator may be used if engineering controls do not maintain airborne contaminant concentrations at a level to adequately protect a workers health.

Eye Protection

None required during normal administration or use of Detachol® Adhesive Remover. When handling large quantities, use approved eye protection to safeguard against potential eye contact.

Protective Clothing Prolonged skin contact may require protective gloves.

Hygienic Work Practices:

Wash hands thoroughly after handling. If working with large quantities of Detachol® Adhesive Remover (such as spill clean-up), use chemical and oil resistant gloves and clothing, and appropriate eye protection. No eating, drinking or smoking in area.



Factor II, Incorporated The Art, Science and Technology of

Safety Data Sheet Product Code: B-206

Revision Date: 7/01/2020

Silicones and Prosthetics...

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (Based on typical material)

- Appearance Odor Odor threshold pH Melting point/freezing point Initial boiling point and boiling range Flash point Evaporation rate Upper/lower flammability or explosive limits
- Vapor pressure Vapor density Relative density Solubility (ies) Partition coeffeiceint: (-octanol/water) Auto-ignition temperature Decomposition temperature Viscosity

SECTION 10: STABILITY AND REACTIVITY DATA

Clear orange liquid Characteristic Not Available Essentially neutral Not Available Not Available > 129°F / > 54°C Not Available Flammable Limits (volume % in air): LEL: 0.7 UEL: 5.3 Not Available Not Available Not Available Not Available Not Available 475°F (246°C) Not Available Not Available

StabilityStable under normal ambient and anticipated
storage and handling conditions of temperature and
pressure.Conditions to avoidAvoid heat, sparks, open flames and other ignition
sources.Materials to avoidAvoid contact with strong oxidizing agents.Hazardous Decomposition ProductsMaterial does not decompose at ambient
temperatures.Hazardous PolymerizationWill not occur.

SECTION 11: TOXICOLOGAICAL INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.



The Art, Science and Technology of Silicones and Prosthetics...

SECTION 12: ECOLOGICAL INFORMATION

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Not expected to be harmful to aquatic organisms or demonstrate chronic toxicity to aquatic organisms.

SECTION 13: DISPOSAL CONSIDERATIONS

For small quantities, product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Disposal of the used product may also be regulated due to ignitability, corrosivity, reactivity or toxicity as determined by the Toxicity Characteristic Leaching Procedure (TCLP). For large quantities, any disposal practice must be in compliance with local, state, and federal laws and regulations (contact local or state environmental agency for specific rules). Do not dispose of via sinks, drains, or into immediate environment.

SECTION 14: TRANSPORT INFORMATION

Regulatory classification of this product varies.

Land (DOT)	Flammable liquid or combustible liquid. This material is not regulated under 49 CFR in a container of 119 gallons or less.
Land (TDG)	Flammable liquid or combustible liquid. This material is not regulated under 49 CFR in a container of 119 gallons or less.
Sea (IMDG)	This product is considered a flammable liquid. Bulk or non-bulk packaging: UN1268, Petroleum Distillates, N.O.S., 3, PG III Finished Product: Shipped under Consumer Commodity
Air (IATA/IMO)	This product is considered a flammable liquid. Bulk or non-bulk packaging: UN1268, Petroleum Distillates, N.O.S., 3, PG III Finished Product: Shipped under Consumer Commodity

SECTION 15: REGULATORY INVORMATION

TSCA Exempt

CERCLA This product contains no components subject to reporting or notification requirements.

SARA (311/312) Reportable Hazard Category Fire



Safety Data Sheet Product Code: B-206 Revision Date: 7/01/2020

The Art, Science and Technology of Silicones and Prosthetics...

SARA (313) Toxic Release Inventory

This product contains no chemicals subject to the supplier notification requirements.

SECTION 16: OTHER INFORAMTION

DISCLAIMER / STATEMENT OF LIABILITY: This is a computer-generated document that is valid without a signature.

The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document.