

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name : Ethyl Acetate

Product Code : B-3808

Intended Use(s): Remover for skin adhesive

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated PO Box 1339 5642 White Mountain Ave Lakeside AZ 85929 928-537-8387 800-332-8688 www.factor2.com sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

Factor II, Incorporate	d	
Americas	:	1 928 368 7502
Europe	:	(+) 1 928 368 7502
Asia Pacific	:	(+) 1 928 368 7502
Middle East / Africa :		(+) 1 928 368 7502
Australia	:	(+) 1 928 368 7502
China	:	(+) 1 928 368 7502

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram





The Art, Science and Technology of Silicones and Prosthetics...

Signal word Danger Hazard statement(s):

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

Formula:	C4H8O2
	 00.44

Molecular weight:	88.11 g/mol
-------------------	-------------

CAS-No.: 141-78-6

EC-No.: 205-500-4

Index-No.: 607-022-00-5



01-2119475103-46-XXXX Registration number:

Hazardous components

Component	Classification	Concentration
Ethyl acetate		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST-AID MEASURES

4.1 **Description of first aid measures**

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: FIRE-FIGHTING MEASURES

5.1 **Extinguishing media**

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

No data available



The Art, Science and Technology of Silicones and Prosthetics...

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated



The Art, Science and Technology of Silicones and Prosthetics...

B-3808 Date of Issue: 09/19/2014 Revision Date: 2/23/2018

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis	
Ethyl acetate	141-78-6	TWA	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
	Remarks	Upper Resp Eye irritation	Upper Respiratory Tract irritation Eve irritation		
		TWA	400.000000 ppm 1,400.000000 mg/m3	USA. NIOSH Recommended Exposure Limits	
		TWA	400.000000 ppm 1,400.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
		The value in	alue in mg/m3 is approximate.		
		TWA	A 400 ppm USA. ACGIH Threshold L (TLV)		
		Upper Resp Eye irritation	espiratory Tract irritation		
		TWA	400 ppm 1,400 mg/m3	USA. NIOSH Recommended Exposure Limits	
		TWA	400 ppm 1,400 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
	The value in mg/m3 is approximate.			nate.	
		PEL	400 ppm 1,400 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)	

Derived No Effect Level (DNEL)

Application Area	Exposure	Health effect	Value
	routes		
Workers	Inhalation	Acute systemic effects	1468 mg/m3
Workers	Inhalation	Acute local effects	1468 mg/m3
Workers	Skin contact	Long-term systemic effects	63mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	734 mg/m3
Workers	Inhalation	Long-term local effects	734 mg/m3
Consumers	Inhalation	Acute local effects, Acute systemic effects	734 mg/m3
Consumers	Skin contact	Long-term systemic effects	37mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	367 mg/m3
Consumers	Ingestion	Long-term systemic effects	4.5mg/kg BW/d
Consumers	Inhalation	Long-term local effects	367 mg/m3



The Art, Science and Technology of Silicones and Prosthetics...

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.24 mg/kg
Marine water	0.026 mg/l
Fresh water	0.26 mg/l
Marine sediment	0.125 mg/kg
Fresh water sediment	1.25 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end ofworkday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 113 min Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail <u>sales@kcl.de</u>, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be

selected according to the concentration and amount of the dangerous substance at the specific workplace.



The Art, Science and Technology of Silicones and Prosthetics...

Safety Data Sheet B-3808 Date of Issue: 09/19/2014 Revision Date: 2/23/2018

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: clear, liquid Colour: colourless		
b) c) d) f) y) h) i)	Odour Odour Threshold pH Melting point/freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability (solid, gas) Upper/lower flammability or explosive limits	No data available No data available No data available -84.0 °C (-119.2 °F) 76.5 - 77.5 °C (169.7 - 171.5 °F) - lit. -3.0 °C (26.6 °F) - closed cup No data available No data available No data available Upper explosion limit: 11.5 %(V) Lower explosion limit: 2.2 %(V)		
k) I) n) o) p)	Vapour pressure Vapour density Relative density Water solubility Partition coefficient: n- octanol/water Auto-ignition	97.3 hPa (73.0 mmHg) at 20.0 °C (68.0 °F) No data available 0.90 g/cm3 at 20 °C (68 °F) soluble log Pow: 0.73 427.0 °C (800.6 °F)		
ten	temperature			
q) r)	Decomposition temperature Viscosity	No data available No data available		

No data available

No data available

- s) Explosive properties
- t) Oxidizing properties

9.2 Other safety information

Surface tension 24.0 mN/m at 20.0 °C (68.0 °F)



SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides Other decomposition products - No data available In the event of fire: see section 5

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 5,620 mg/kg LC50 Inhalation - Mouse - 2 h - 45,000 mg/m3 LD50 Dermal - Rabbit - > 18,000 mg/kg No data available

Skin corrosion/irritation

Skin - Rabbit Result: Mild skin irritation (OECD Test Guideline 404)

Serious eye damage/eye irritation Respiratory or skin sensitisation No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH,

NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.



The Art, Science and Technology of Silicones and Prosthetics...

NTP:

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA:

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: AH5425000 Inhalation of high concentrations may cause:, Headache, Drowsiness, Dizziness, Vomiting, narcosis, anemia, Central nervous system depression Kidney - Irregularities - Based on Human Evidence Kidney - Irregularities - Based on Human Evidence

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 350.00 - 600.00 mg/l - 96 h LC50 - Pimephales promelas (fathead minnow) - 220.00 - 250.00 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 2,300.00 - 3,090.00 mg/l - 24 h

Toxicity to algae

LC50 - Daphnia magna (Water flea) - 560 mg/l - 48 h EC50 - Algae - 4,300.00 mg/l - 24 h EC50 - SELENASTRUM - 1,800.00 - 3,200.00 mg/l - 72 h

12.2 Persistence and degradability

Biodegradability

Result: 79 % - Readily biodegradable (OECD Test Guideline 301D)



The Art, Science and Technology of Silicones and Prosthetics...

12.3 Bioaccumulative potential

Bioaccumulation - 3 d Bioconcentration factor (BCF): 30

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

SECTION 14: TRANSPORT INFORMATION

DOT (US)

UN number: 1173 Class: 3 Proper shipping name: Ethyl acetate Reportable Quantity (RQ): 5000 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1173 Class: 3 Proper shipping name: ETHYL ACETATE

ΙΑΤΑ

UN number: 1173 Class: 3 Proper shipping name: Ethyl acetate Packing group: II

Packing group: II EMS-No: F-E, S-D

Packing group: II

SECTION 15: REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



Safety Data Sheet B-3808 Date of Issue: 09/19/2014 Revision Date: 2/23/2018

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Ethyl acetate	141-78-6	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Ethyl acetate	141-78-6	1993-04-24
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Ethyl acetate	141-78-6	1993-04-24

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. STOT SE Specific target organ toxicity - single exposure

HMIS Rating

Reactivity Hazard:

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0
NFPA Rating	
Health hazard:	2
Fire Hazard:	3

DISCLAIMER / STATEMENT OF LIABILITY:

0

Factor II, Inc. urges each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology and/or fire prevention as necessary or appropriate to the use and understanding of the data contained in this SDS. To promote safe handling each customer or recipient should 1) notify and furnish its employees, agents, contractors, customers and/or others whom it knows or believes will use this material of the information regarding hazards or safety, and 2) request its customers to notify their employees, customers and other users of the product of this information.