



SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name : Secure Solvent

Product Code : B-508

Intended Use(s) : Cleaning silicone adhesive residue from the prosthesis and skin

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated PO
Box 1339
5642 White Mountain Ave Lakeside
AZ 85929
928-537-8387
800-332-8688
www.factor2.com
sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

Factor II, Incorporated 1 928 368 7502

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Classification Flammable Liquids Category 3

Aspiration Hazard Category 1

Eye Irritation Category 2B

Skin Irritation Category 2

Specific Target Organ Toxicity-Single Exposure (narcotic effects) –
Category 3

Static Accumulating Liquid

Signal Word DANGER!

Hazard Statements Flammable liquid and vapor

May be fatal if swallowed and enters airways.

Causes eye irritation

Causes skin Irritation

May cause respiratory irritation; or May cause drowsiness or
dizziness

Other Hazard Information Static accumulating liquid can become electrostatically charged even
in bonded and grounded equipment

Sparks may ignite liquid and vapor may cause flash fire.

Liquid conductivity is <100 pS/m (picosiemens/meter) at 77°F



GHS Pictogram



Precautionary Statements

Do not breathe mist or vapors
 Use only outdoors or in a well-ventilated area
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 If swallowed: immediately call a poison center or doctor.
 Do NOT induce vomiting.
 Store Locked up
 Store in a well-ventilated place.
 Wear protective gloves/clothing/eye protection/face protection
 Keep away from heat/sparks/open flames/hot surfaces.
 –No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment. This alone may be insufficient to remove static electricity.
 Use explosion-proof electrical/ventilating/lighting equipment.
 Use only non-sparking tools
 If on skin: take of immediately all contaminated clothing.
 Rinse skin with water/shower.
 Store in a well-ventilated place. Keep cool.
 Wash thoroughly after handling.
 If in eyes: rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: get medical attention/advice.
 If skin irritation occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Dispose of contents in accordance with local /regional /national/ international regulations

Hazardous Ingredient	CAS Number	Concentration (%)
Stoddard solvent	8052-41-3	>=90 - <=100

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

SECTION 4: FIRST-AID MEASURES

Eyes

Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.



Skin

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

Move exposed person to fresh air.

Ingestion

DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water.

Symptoms(Acute and delayed)

Exposure to high concentrations of vapors may cause irritation to the eyes, nose and throat, nausea, and dizziness.

Note to Physicians No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Unsuitable Extinguishing Media

Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating vapors. Decomposing products may include the following materials: Carbon dioxide and Carbon monoxide.

This product is a static accumulating liquid. Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Restrict flow velocity to avoid build-up of static charge. Refer to NFPA 77, API 2003, and CENELEC CLC/TR 50404 for further guidance.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas.

Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.



Environmental Precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods for Containment

Stop leak if without risk. Use absorbent pads or earthen dams to contain.

Methods for Cleanup

A vapor suppressing foam may be used to reduce vapors. Cover liquid spill with sand, earth or other noncombustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled container

SECTION 7: HANDLING AND STORAGE

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

Shipping and Storing Procedures

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous.

Incompatibilities:

Oxidizing Agents

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Stoddard Solvent

ACGIH TLV:	TWA: 100 ppm	TWA: N/A mg/m ³	STEL: N/A ppm	STEL: N/A mg/m ³
OSHA PEL:	TWA: 500 ppm	TWA 2900	STEL: N/A ppm	STEL: N/A mg/m ³
		mg/m ³		
NIOSH REL:	TWA: N/A ppm	TWA 350 mg/m ³	STEL: N/A ppm	STEL: N/A mg/m ³
NIOSH Ceiling:	1800 mg/m ³ (15 minutes)			

Engineering Controls This product is a static accumulating liquid. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Material should be handled in enclosed vessels and equipment. Use only in adequate ventilation. Use process enclosures, local



exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Eye/Face Protection Chemical goggles and face shield.

Skin Protection Chemical resistant, impervious gloves complying with an approved standard should be worn at all times. Coveralls, apron, and boots as necessary to minimize contact.

Respiratory Protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicated this is necessary. Respirator selection must be based on known or anticipated exposure levels.

General Hygiene Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
--

Appearance	Colorless	Flammability	Flammable Liquid and vapor
Physical State	Liquid	Upper/Lower Flammability Limits	Upper: 7.5% Lower: 1.0%
Odor	Petroleum Solvent	Vapor Pressure (mm Hg at 20°C)	0.62
Odor Threshold	Not Available	Vapor Density	Not Available
pH	Not Available	Relative Density (lbs/gal)	6.43
Melting/Freezing Point (°F)	Not Available	Water Soluble	No
Initial Boiling Point (°F)	310	Partition Coefficient: n-octanol/water	Not Available
Boiling Range (°F)	310-393	Auto-ignition Temperature (°F)	752
Flash Point (°F) Tag Closed Cup ASTM D-56	105	Decomposition Temperature (°F)	Not Available
Evaporation Rate	Not Available	Viscosity (40°C mm²/s)	1.8
Volatile Organic Compounds (g/L)	770.3	Aromatic Content (Typical Vol %)	10.5

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Polymerization will not occur

Chemical Stability

Stable under normal conditions. If heated, product's static accumulation will rise and could cause



flash fire.

Hazardous Reactions

None, under normal processing.

Conditions to Avoid

High temperatures, flames, sparks

Incompatibility

Strong acids and oxidizing materials

Hazardous Decomposition Products

Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Exposure

Respiratory Irritation

An inhalation hazard may only arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and upper respiratory tract.

Eye Irritation

Causes mild eye irritation that is reversible with proper care.

Skin Irritation

Causes mild skin irritation that is reversible with proper care.

Sensitization

Not expected to cause skin or respiratory sensitization.

Aspiration Hazard

If swallowed can be aspirated into lungs and cause chemical pneumonia, varying degrees of pulmonary injury or death. If swallowed, do NOT induce vomiting.

Chronic Exposure

Target Organ Effects

Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death. Prolonged or repeated direct exposure to the skin results in symptoms of irritation and redness, dermatitis or oil acne.

Carcinogenicity

No data available to indicate product or any components present at greater than .1% are carcinogenic.

Mutagenicity

No data available to indicate product or any components present at greater than .1% are



mutagenic or genotoxic.

Reproductive Toxicity

No data available to indicate either product or components present at greater than .1% that may cause reproductive toxicity.

Teratogenicity No data available to indicate product or any components contained at greater than .1% may cause birth defects.

Analysis – LD50 / LC50

Inhalation LC50 Rat	>5 mg/L (4Hr mist)
Oral LD50 Rat	>5000 mg/kg
Dermal LD50 Rabbit	>2000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Component Analysis- Ecotoxicity – Aquatic Life

Duration/Test/Species	Concentration/Conditions
96 hr LL50 <i>Oncorhyncus mykiss</i>	8.2 mg/L
48 hr EL50 <i>Oncorhyncus mykiss</i>	32 mg/L
96 hr EL50 <i>Scenedesmus subspicatus</i>	45 mg/L
Chronic Survival NOELR Aquatic Vertebrates	2.6 mg/L
Chronic Growth NOELR Aquatic Vertebrates	2.6 mg/L
Chronic Survival NOELR <i>Daphnia magna</i>	16 mg/L
Chronic Reproduction EL 50 <i>Daphnia magna</i>	10 mg/L
Chronic reproduction NOELR <i>Daphnia magna</i>	2.6 mg/L

Persistence & Degradability

Inherently biodegradable

Bioaccumulation Potential

Not Available

Soil Mobility

Not Available

Other Adverse Effects

Not Available






SECTION 13: DISPOSAL CONSIDERATIONS

Disposal Instructions

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

SECTION 14: TRANSPORT INFORMATION

Emergency Response Guide No. 128 *North American Emergency Response Guide Book*

	UN Number	Shipping Name (technical name)	Hazard Class	Packing Group	Labels/ Plackard
U.S. DOT Bulk (over 119 gallons)	1268	Petroleum Distillates, N.O.S. (Naphtha Solvent)	Combustible Liquid	III	
U.S. DOT Non-Bulk		Not Regulated			Exempt
IATA	1268	Petroleum Distillates, N.O.S. (Naphtha Solvent)	3	III	
IMDG	1268	Petroleum Distillates, N.O.S. (Naphtha Solvent)	3	III	
STCC		4914256			

SECTION 15: REGULATORY INFORMATION

SARA Extremely Hazardous Substances (Sections 302 & 304)

This product does not contain greater than 1% of any “extremely hazardous substances” listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA Section 311 & 312 Classifications

Physical Hazards Yes

Flammable Liquid

Static Accumulating Liquid

Health Hazards Yes

Aspiration Hazard Eye Irritant

Skin Irritant



Specific Target Organ Toxicity

CERCLA

This product contains the following components listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4:
NONE

California Prop 65

This product is not routinely tested to determine chemical(s) known to the state of California to cause cancer and/or birth defects based on maximum impurity levels of components.

California Air Resource 15

Board (CARB) Bin Number

Global Chemical Inventories

Inventory	
US TSCA	Present*
EU	Present
Japan	Not available
Australia	Present
New Zealand	Present
Canada	Present
Switzerland	Not available
Korea	Present
Philippines	Present
China	Present
Taiwan	Not available

SECTION 16: OTHER INFORMATION

US NFPA Ratings

Health	Fire	Reactivity
1	2	0

HMIS Ratings

Health	Fire	Physical Hazard
1	2	0

PATENT WARNING:

Factor II Technology disclaims any expressed or implied warranty against the infringement of any patent. Factor II does not warrant that the use or sale of the products described herein will not infringe the claims of any U.S. patents or other country's patents covering the product itself or the use in combination with other products or in the operation of any process.

WARNINGS ABOUT PRODUCT SAFETY:

Factor II technology believes that the information and data contained herein is accurate and reliable; however, it is the user's responsibility to determine suitability and safety of use for these materials.

Factor II cannot know the specific requirements of each application and hereby makes the user aware that it has not



tested or determined that these materials are suitable or safe for any application. It is the user's responsibility to adequately test and determine the safety and suitability for their application. Factor II makes no warranty concerning fitness for any use or purpose. There has been no testing done by Factor II to establish safety of use in any medical application. Factor II has tested this material only to determine if the product meets the applicable specification. When considering the use a Factor II product in a particular application, you should review the latest Material Safety Data Sheets and contact Factor II for any questions about product safety information you may have.

IT IS RECOMMENDED THAT THE PURCHASER THOROUGHLY TEST ANY APPLICATION PRIOR TO FULL SCALE PRODUCTION OR COMMERCIALIZATION. INFORMATION CONTAINED IN THIS TECHNICAL PROFILE SHOULD NOT BE TAKEN AS INDUCEMENT TO FRINGE ANY PATENT. FACTOR II WARRANTS ONLY THAT ITS PRODUCTS MEET ITS SPECIFICATIONS. THERE IS NO WARRANTY OF MERCHANTABILITY OF FITNESS FOR USE OR ANY OTHER WARRANTIES EXPRESS OR IMPLIED. FACTOR II MAKES NO GUARANTEE OF SATISFACTORY RESULTS

DISCLAIMER / STATEMENT OF LIABILITY:

This is to certify that the above designated material has been tested and did comply with the listed specifications (with listed exceptions) when supplied in original container. The material is subject to the conditions listed on the invoice. The above is a copy of information on file. The lot acceptance data are available for examination. This is a computer-generated document that is valid without a signature. The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document. Factor II is a distributor of this product not the manufacture. Factor II will warrant this product 6-months from the ship date, some restrictions apply.