

Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

SECTION 1: IDENTIFICATION

PRODUCT IDENTIFIER

Product Name: Impression Lubricant

Product Code : FX-300

Intended Use(s): For professional use only

CONTACT INFORMATION FOR SUPPLIER OF SAFETY DATA SHEET

Factor II, Incorporated 5642 White Mountain Ave PO Box 1339 Lakeside AZ 85929 928-537-8387 www.factor2.com sales@factor2.com

EMERGENCY TELEPHONE NUMBERS

928-368-7502

SECTION 2: COMPOSITION AND INFORMATION ON INGREDIENTS

Composition:

Name	CAS#	% by Weight
Cholesterol	57-88-5	100

Toxicological Data on Ingredients:Cholesterol LD50
Not available
LC50
Not available

SECTION 3: HAZARD IDENTIFICATION

Potential Acute Health Effects:

Slightly hazardous in case of skin contact (irritant, permeator), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

Slightly hazardous in case of ingestion. CARCINOGENIC EFFECTS: 3 (Not classifiable for human.) by IARC. MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available.



Silicones and Prosthetics...

Safety Data Sheet

Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

The substance may be toxic to blood, liver. Repeated or prolonged exposure to the substance can produce target organs damage.

SECTION 4: FIRST-AID MEASURES

Eye Contact: Check for and remove any contact lenses. In case of contact,

immediately flush eyes with plenty of water for at least 15 minutes.

Cold water may be used. WARM water MUST be used. Get

medical attention if irritation occurs.

Skin Contact: Wash with soap and water. Cover the irritated skin with an

emollient. Get medical attention if irritation develops.

Serious Skin Contact: Not available.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen. Get medical

attention.

Serious Inhalation: Not available.

Ingestion: Do NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie,

belt or waistband.

Serious Ingestion: Not available.

SECTION 5: FIRE-FIGHTING MEASURES

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Points: Not available.

Flammable Limits: Not available.

Products of Combustion: These products are carbon oxides (CO, CO2).

Fire Hazards in Presence of Various Substances:

Slightly flammable to flammable in presence of heat.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use water spray, fog or foam. Do not use water jet.



Silicones and Prosthetics...

Safety Data Sheet

Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Small Spill:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Large Spill:

Use a shovel to put the material into a convenient waste disposal container. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system.

SECTION 7: HANDLING AND STORAGE

Precautions:

Keep away from heat. Keep away from sources of ignition and equipment containing material. Do not breathe dust. Wear suitable protective clothing. If you feel unwell, seek medical attention and show the label when possible. Keep away from incompatibles such as oxidizing agents.

Storage:

Keep container tightly closed. Keep container in a cool, well-ventilated area. Sensitive to light. Store in light-resistant containers

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection:

Safety glasses. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Dust respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.



Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

Exposure Limits: Not available.

Silicones and Prosthetics...

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance: Solid. (crystalline powder.)

Odor:almost odorless.Taste:Not available.Molecular Weight:386.67 g/mole

Color: White.

pH (1% soln/water): Not available.
Boiling Point: 360°C (680°F)

Melting Point: 148°C (298.4°F) - 150 C.

Critical Temperature: Not available. **Specific Gravity:** 1.067 (Water = 1)**Vapor Pressure**: Not applicable. Vapor Density: Not available. Volatility: Not available. **Odor Threshold:** Not available. Water/Oil Dist. Coeff.: Not available. Ionicity (in Water): Not available.

Dispersion Properties: See solubility in water, diethyl ether, acetone.

Solubility:

Soluble in diethyl ether, acetone. Very slightly soluble in cold water. Solubility in water: 0.2mg/100ml or 0.2% Slightly soluble in alcohol; more soluble in hot alcohol. Soluble in chloroform, pyridine, benzene, petroleum ether, oils, fats, aqueous solutions of bile salts. Solubility in ether: 1 g/2.8 ml ether. Solubility in chloroform: 1 g/4.5 ml chloroform.

Solubility in pyridine: 1 g/1.5 ml pyridine.

SECTION 10: STABILITY AND REACTIVITY

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Excess heat, incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents.


Corrosivity: Not considered to be corrosive for metals and

alass.

Special Remarks on Reactivity: Sensitive to light. Air sensitive. It is affected by light

and air and turns yellow.

Special Remarks on Corrosivity: Not available.



Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

Polymerization: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Routes of Entry: Absorbed through skin. Inhalation.

Ingestion.

Toxicity to Animals: LD50: Not available.

LC50: Not available.

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: 3 (Not classifiable for human.) by IARC. MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. May cause damage to the following organs: blood, liver.

Other Toxic Effects on Humans:

Slightly hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

May cause adverse reproductive effects and birth defects (teratogenic) based on animal test data. No human data found. May affect genetic material (mutagenic)

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects:

Skin: May cause skin irritation. It may be absorbed through the skin.

Low hazard for usual industrial handling.

Eyes: May cause mechanical eye irritation.

Inhalation: May cause respiratory tract irritation. Low hazard for usual

industrial handling.

Ingestion: Ingestion of large amounts may cause gastrointestinal tract

irritation with nausea, vomiting, diarrhea. Expected to be a low


hazard for usual industrial handling.

Chronic Potential Health Effects:

Ingestion: Cholesterol is the principal sterol found in the body tissues of

higher animals. Toxicity only seems to occur only after prolonged oral doses of medium to high amounts. Prolonged or repeated ingestion may affect the liver (changes in liver weight), spleen (changes in spleen weight), and blood (changes in serum composition; pigmented or nucleated red blood cells).

Other symptoms noted in the Registry of Toxic Effects of Chemical Substances include changes in cochlear function and structure, and changes in peripheral motor recordings. The toxicological properties in this substance have not been fully investigated.



Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short-term degradation products are not likely.

However, long term degradation products may arise.

Toxicity of the Products of Biodegradation:

The product itself and its products of degradation are not toxic.

Special Remarks on the Products of Biodegradation: Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Waste must be disposed of in accordance with federal, state and

local environmental control regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Classification: Not a DOT controlled material (United States).

Identification: Not applicable.

Special Provisions for Transport: Not applicable.

SECTION 15: REGULATORY INFORMATION

Federal and State Regulations:

TSCA 8(b) inventory: Cholesterol

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR

910.1200).

EINECS: This product is on the European Inventory of Existing Commercial

Chemical Substances.

Other Classifications:

WHMIS (Canada): Not controlled under WHMIS (Canada).

DSCL (EEC): Not applicable Not applicable.



Factor II, Incorporated

The Art, Science and Technology of Silicones and Prosthetics...

Safety Data Sheet

Product Code A-415

Date of issue: 06-09-2012 Revision Date: 05-05-2019

HMIS (U.S.A.):

Health Hazard: 1 Fire Hazard: 1 Reactivity: 0

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 1 Reactivity: 0 Specific hazard:

Protective Equipment:

Gloves. Lab coat. Dust respirator. Be sure to use an approved/certified respirator or equivalent. Safety glasses.

SECTION 16: OTHER INFORMATION

DISCLAIMER / STATEMENT OF LIABILITY:

This is a computer-generated document that is valid without a signature.

The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document.