



Factor II, Incorporated

Inventing and Innovating...
(Information: 1.928.537.8387)
ONLINE ORDERING www.factor2.com

PRODUCT INFORMATION

A-4717

HIGH TACK SILICONE GEL

PRODUCT DESCRIPTION

Factor II Inc. A-4717 silicone Elastomer is a two part, clear to translucent, pourable silicone system which will cure at room temperature. Cure time can be reduced with elevated temperatures. The silicone material is delivered as two low viscous liquid components, which once mixed and cured, transform into an elastic gel. Polymerization occurs without formation of heat.
Posterior Surface of Silicone, Prosthesis- Adhesive back (no adhesive necessary)

ADVANTAGES:

Very good adhesion on dry skin
No adhesion on moist wounds
Proven biocompatibility
No free oil

CHARACTERISTICS OF NON CURED PRODUCT

Color	Translucent
Appearance	Viscous liquid
Viscosity A	60,000 cps
Density	0.98
Working Time @ 23°C	2 hours

CHARACTERISTICS OF CURED PRODUCT

Penetration (mm/10), hollow cone (62.5)g	170
Probe Tack 0.25 mm layer, approx.	9.0

MIXING:

A-4717 Part A and Part B are mixed in a 1:1 ratio by weight. Care should be taken to minimize air entrapment during mixing. Vacuum deairation at 28 inches Hg is recommended. Apply vacuum to a container at least four times the volume of the material to avoid overflow of the bubbles. Allow the material to reach it's maximum capacity , and fall to the bottom of the container. Continue to hold the vacuum for 3 to 5 minutes. This will eliminate the smaller bubbles. When packing the material into a mold, care should be taken to minimize trapping air bubbles.

CONTAINERS:

When mixing A-4717 use clean containers such as glass, stainless steel, or a 16 or 20oz polypropylene container with a stainless steel spatula

POLYMERIZATION:

A-4717 will cure in contact with most materials. Exceptions include natural rubbers, some RTV silicones ie: tin cured systems, Epoxy resins catalyzed with amines.



Factor II, Incorporated

Inventing and Innovating...
(Information: 1.928.537.8387)
ONLINE ORDERING www.factor2.com

STORAGE AND SHELF LIFE:

Factor II warrants products for 6 months from the date of shipment when stored in original containers unopened a room temperature 25 C (77 F)

PATENT WARNING:

Factor II Technology disclaims any expressed or implied warranty against the infringement of any patent. Factor II does not warrant that the use or sale of the products described herein will not infringe the claims of any U.S. patents or other country's patents covering the product itself or the use in combination with other products or in the operation of any process.

WARNINGS ABOUT PRODUCT SAFETY:

Factor II technology believes that the information and data contained herein is accurate and reliable; however, it is the user's responsibility to determine suitability and safety of use for these materials.

Factor II cannot know the specific requirements of each application and hereby makes the user aware that it has not tested or determined that these materials are suitable or safe for any application. It is the user's responsibility to adequately test and determine the safety and suitability for their application. Factor II makes no warranty concerning fitness for any use or purpose. There has been no testing done by Factor II to establish safety of use in any medical application. Factor II has tested this material only to determine if the product meets the applicable specification. When considering the use a Factor II product in a particular application, you should review the latest Material Safety Data Sheets and contact Factor II for any questions about product safety information you may have.

IT IS RECOMMENDED THAT THE PURCHASER THOROUGHLY TEST ANY APPLICATION PRIOR TO FULL SCALE PRODUCTION OR COMMERCIALIZATION. INFORMATION CONTAINED IN THIS TECHNICAL PROFILE SHOULD NOT BE TAKEN AS INDUCEMENT TO FRINGE ANY PATENT. FACTOR II WARRANTS ONLY THAT ITS PRODUCTS MEET ITS SPECIFICATIONS. THERE IS NO WARRANTY OF MERCHANTABILITY OF FITNESS FOR USE OR ANY OTHER WARRANTIES EXPRESS OR IMPLIED. FACTOR II MAKES NO GUARANTEE OF SATISFACTORY RESULTS

DISCLAIMER / STATEMENT OF LIABILITY:

This is to certify that the above designated material has been tested and did comply with the listed specifications (with listed exceptions) when supplied in original container. The material is subject to the conditions listed on the invoice. The above is a copy of information on file. The lot acceptance data are available for examination. This is a computer-generated document that is valid without a signature. The information above is supplied in good faith and, to the best of our knowledge, is based on available sources believed to be reliable and accurate. This document and any information provided herein are for your guidance only. The use by the requestor is beyond Factor II control; therefore, the responsibility for appropriate and safe use of the above information lies with the End user. Factor II shall not be responsible for any misuse and/or misapplication of the information in this document. Factor II will guarantee this product 6-months from the ship date, some restrictions apply.